upon appropriate criteria such as statistical criteria for component variability, confidence levels, and degree of precision desired, the past quality history of the supplier, and the quantity needed for analysis and reserve where required by §211.170.

- (c) Samples shall be collected in accordance with the following procedures:
- (1) The containers of components selected shall be cleaned where necessary, by appropriate means.
- (2) The containers shall be opened, sampled, and resealed in a manner designed to prevent contamination of their contents and contamination of other components, drug product containers, or closures.
- (3) Sterile equipment and aseptic sampling techniques shall be used when necessary.
- (4) If it is necessary to sample a component from the top, middle, and bottom of its container, such sample subdivisions shall not be composited for testing.
- (5) Sample containers shall be identified so that the following information can be determined: name of the material sampled, the lot number, the container from which the sample was taken, the date on which the sample was taken, and the name of the person who collected the sample.
- (6) Containers from which samples have been taken shall be marked to show that samples have been removed from them.
- (d) Samples shall be examined and tested as follows:
- (1) At least one test shall be conducted to verify the identity of each component of a drug product. Specific identity tests, if they exist, shall be used.
- (2) Each component shall be tested for conformity with all appropriate written specifications for purity, strength, and quality. In lieu of such testing by the manufacturer, a report of analysis may be accepted from the supplier of a component, provided that at least one specific identity test is conducted on such component by the manufacturer, and provided that the manufacturer establishes the reliability of the supplier's analyses through

appropriate validation of the supplier's test results at appropriate intervals.

- (3) Containers and closures shall be tested for conformance with all appropriate written procedures. In lieu of such testing by the manufacturer, a certificate of testing may be accepted from the supplier, provided that at least a visual identification is conducted on such containers/closures by the manufacturer and provided that the manufacturer establishes the reliability of the supplier's test results through appropriate validation of the supplier's test results at appropriate intervals.
- (4) When appropriate, components shall be microscopically examined.
- (5) Each lot of a component, drug product container, or closure that is liable to contamination with filth, insect infestation, or other extraneous adulterant shall be examined against established specifications for such contamination.
- (6) Each lot of a component, drug product container, or closure that is liable to microbiological contamination that is objectionable in view of its intended use shall be subjected to microbiological tests before use.
- (e) Any lot of components, drug product containers, or closures that meets the appropriate written specifications of identity, strength, quality, and purity and related tests under paragraph (d) of this section may be approved and released for use. Any lot of such material that does not meet such specifications shall be rejected.

 $[43\ FR\ 45077,\ Sept.\ 29,\ 1978,\ as\ amended\ at\ 63\ FR\ 14356,\ Mar.\ 25,\ 1998]$

§211.86 Use of approved components, drug product containers, and closures.

Components, drug product containers, and closures approved for use shall be rotated so that the oldest approved stock is used first. Deviation from this requirement is permitted if such deviation is temporary and appropriate.

§211.87 Retesting of approved components, drug product containers, and closures.

Components, drug product containers, and closures shall be retested or

§ 211.89

reexamined, as appropriate, for identity, strength, quality, and purity and approved or rejected by the quality control unit in accordance with §211.84 as necessary, e.g., after storage for long periods or after exposure to air, heat or other conditions that might adversely affect the component, drug product container, or closure.

§211.89 Rejected components, drug product containers, and closures.

Rejected components, drug product containers, and closures shall be identified and controlled under a quarantine system designed to prevent their use in manufacturing or processing operations for which they are unsuitable.

§211.94 Drug product containers and closures.

- (a) Drug product containers and closures shall not be reactive, additive, or absorptive so as to alter the safety, identity, strength, quality, or purity of the drug beyond the official or established requirements.
- (b) Container closure systems shall provide adequate protection against foreseeable external factors in storage and use that can cause deterioration or contamination of the drug product.
- (c) Drug product containers and closures shall be clean and, where indicated by the nature of the drug, sterilized and processed to remove pyrogenic properties to assure that they are suitable for their intended use.
- (d) Standards or specifications, methods of testing, and, where indicated, methods of cleaning, sterilizing, and processing to remove pyrogenic properties shall be written and followed for drug product containers and closures.

Subpart F—Production and Process Controls

§ 211.100 Written procedures; deviations.

(a) There shall be written procedures for production and process control designed to assure that the drug products have the identity, strength, quality, and purity they purport or are represented to possess. Such procedures shall include all requirements in this

subpart. These written procedures, including any changes, shall be drafted, reviewed, and approved by the appropriate organizational units and reviewed and approved by the quality control unit.

(b) Written production and process control procedures shall be followed in the execution of the various production and process control functions and shall be documented at the time of performance. Any deviation from the written procedures shall be recorded and justified.

§211.101 Charge-in of components.

Written production and control procedures shall include the following, which are designed to assure that the drug products produced have the identity, strength, quality, and purity they purport or are represented to possess:

- (a) The batch shall be formulated with the intent to provide not less than 100 percent of the labeled or established amount of active ingredient.
- (b) Components for drug product manufacturing shall be weighed, measured, or subdivided as appropriate. If a component is removed from the original container to another, the new container shall be identified with the following information:
- (1) Component name or item code;
- (2) Receiving or control number;
- (3) Weight or measure in new container;
- (4) Batch for which component was dispensed, including its product name, strength, and lot number.
- (c) Weighing, measuring, or subdividing operations for components shall be adequately supervised. Each container of component dispensed to manufacturing shall be examined by a second person to assure that:
- (1) The component was released by the quality control unit;
- (2) The weight or measure is correct as stated in the batch production records;
- (3) The containers are properly identified.
- (d) Each component shall be added to the batch by one person and verified by a second person.